


PERFORMANCE

• Working Height	7.72 m
• Platform Height – Elevated	5.72 m
A. Stowed Height	2.02 m
B. Platform Railing Height	1.10 m
C. Stowed Height (Rails Folded) 1	1.59 m
D. Platform Size (W x L)	0.76 m x 1.87 m
E. Deck Extension	0.90 m
F. Overall Width	0.76 m
G. Overall Length	1.87 m
H. Wheelbase	1.60 m
I. Ground Clearance	0.09 m
• Platform Capacity 2	230 kg
• Capacity on Optional Deck Extension	120 kg
• Lift/Lower Time	20/30 sec.
• Maximum Drive Height	5.72 m
• Machine weight 3	1,565 kg
• Maximum Ground Bearing Pressure	8.73 kg/cm ²
• Drive Speed - Lowered	4.8 km/h
• Gradeability	25%
• Turning Radius – Inside	Zero
• Turning Radius – Outside	1.75 m



DIMENSIONS





Model 1930ES SCISSOR LIFTS

MORE ECONOMIC

- Electric power for zero emissions and near-silent running indoors.

MORE PRODUCTIVE

- Boost efficiency with direct electric drive.

MORE ACCESS

- Get into more places with compact dimensions and precise control system.

SMART DESIGN

- Enjoy industry leading upcycles so you can work longer with higher productivity.

SMART DESIGN

- Enjoy industry leading upcycles so you can work longer with higher productivity.

STANDARD FEATURES

- 0.90 m roll-out deck extension
- Fold Down Handrails
- Half swing gate
- Removable platform console box
- Lanyard attach points
- Full proportional drive joystick control with integral thumb steer switch
- Proportional lift/lower speed control
- Joystick enable for lift and drive
- Load sensing system
- Automatic positive traction
- Programmable "Personality" settings
- On-board self-diagnostic testing
- Swing-out battery/electrical compartment doors
- 20 amp automatic battery charger
- Dual motor direct electric front wheel drive & steer
- Dual wheel automatic brakes
- Emergency brake release
- Pothole protection system
- AC cable to platform
- Battery condition indicator
- Hour meter
- Lubrication free scissor arm bushings
- Scissor maintenance prop
- Manual descent
- Horn
- Slope alarm and light
- Tie down lugs
- Fork lift pockets

STANDARD SPECIFICATIONS

- | | |
|--------------------------------|-------------------|
| • Tyres (Non-Marking Solid) | 323 x 100 |
| • Drive | 24V Electric 6 kW |
| • Deep Cycle Batteries | 4 x 6V 220 A/hr |
| • Charger (120/240V – 50/60HZ) | 20 Amp Automatic |
| • Hydraulic System | 8.3 L |

ACCESSORIES & OPTIONS

- | | |
|-----------------------------|---|
| • 13mm air line to platform | • Workstation c/w 12V outlet |
| • Platform work-lights | • Workstation w/o 12V outlet |
| • 220 A/hr AGM Batteries | • Amber strobe light |
| • Lifting lugs | • Euro Plug & Socket |
| • All motion alarm | • Synthetic Biodegradable Hydraulic Oil |
| • Descent alarm | • Electrician Tree |
| • Alarm package 1 | • Special paint colour |
| • Platform padding | |

1 Includes all-motion alarm + amber strobe light.
Certain options or country standards may increase weight and/or dimensions.

